



# MOORLASTIC<sup>®</sup>

## TUB AND TILE CAULK 469

### Features

- Siliconized
- Extremely flexible
- Excellent adhesion to common surfaces
- Cured caulk is mildew resistant
- Interior/Exterior
- Will not crack, lose adhesion or discolor
- Soap and water clean-up

### Recommended For

Use to seal around tubs, wash stands, shower doors, windows, fixtures and for resetting loose tiles and as replacement grout. Also excellent for boat use.

### General Description

Moorlastic<sup>®</sup> Tub & Tile Caulk (469) is an adhesive caulk made from a special formulation of several elastomeric latex copolymers, combined with silicone and other selected ingredients. It is easy to apply, dries quickly, will seal up to 1/2" wide openings. May be painted over with Benjamin Moore<sup>®</sup> solvent or latex based paint products when dry.

### Limitations

- Do not apply when air and surface temperatures are below 50°F (10°C)
- Not intended for use underwater
- Shelf Life 12 months

### Product Information

#### Colors — Standard:

White (01)

#### — Tint Bases:

Not available

#### — Special Colors:

Contact your Benjamin Moore representative.

#### Certification

**VOC compliant in all regulated areas.**

VOC STATEMENT: "Non-Chemically Curing Non-Aerosol Caulk"

#### Technical Assistance:

Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

#### Technical Data<sup>∅</sup>

#### White

Vehicle Type Vinyl Acetate Complex Resin

Pigment Type Titanium Dioxide

Volume Solids 62%

Coverage per Gallon at Recommended Film Thickness One tube will caulk two average tubs

Recommended Film Thickness — Wet mils  
— Dry mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint (Minimum depending on climatic conditions and bead width).

Dry Time @ 77°F — To Touch 30 Minutes  
(25°C) @ 50% RH — To Recoat 4 – 6 Hours

High humidity and cool temperatures will result in longer dry, recoat and service times.

Dries By Evaporation, Coalescence

Viscosity N/A

Flash Point None

Gloss / Sheen N/A

Surface Temperature — Min. 50°F  
at Application — Max 90°F

Thin With Do Not Thin

Clean Up Thinner Clean Water

Weight Per Gallon 10.9 lbs

Storage Temperature — Min. 40°F  
— Max 90°F

Volatile Organic Compounds (VOC)

This product is formulated not to exceed:  
25 Grams/Liter and 1.5% VOC/Weight

<sup>∅</sup> Reported values are for White.

## **Surface Preparation**

Surface must be clean, dry and free from dirt, dust, grease, oil, mildew, wax, loose paint and old caulking. Stains from mildew must be removed by cleaning with Benjamin Moore® Clean (318) prior to application of this product. **Caution:** Refer to the (318) Clean technical data and material safety data sheets for instructions on its proper use and handling. Prime bare substrates with the recommended Benjamin Moore® primer prior to caulk application. Apply only when caulk, air and substrate temperatures are above 50°F.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

## **Application**

Remove cap and trim nozzle to desired bead size. Apply evenly; smooth bead gently with wet finger and wipe excess with a damp cloth. Allow to dry at least 72 hours before exposure to water.

## **Thinning/Cleanup**

**Do not thin.**

Wash tools and hands with warm, clean water immediately after use and before compound dries.

USE COMPLETELY OR DISPOSE OF PROPERLY. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

## **Environmental, Health & Safety Information**

**Use only with adequate ventilation.** Do not breathe vapors. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application. Close container after each use. Wash thoroughly after handling.

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**FIRST AID:** In case of eye contact, flush with water for 15 minutes; for skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Spilled or excess material can be scraped up and disposed of as specified under “Clean Up”.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for  
additional health and safety information.**