



# STUDIO FINISHES® CHALKBOARD PAINT K307

## Features

- Studio Finishes® Chalkboard paint (K307) is a topcoat that turns any interior surface into a chalkboard
- Goes on easily and is washable
- Resists spattering during application
- Dries to a decorative finish that is extremely durable
- Is formulated to minimize lingering odours
- Soap and water clean-up
- Dries quickly

## Recommended For

For interior use on previously painted surfaces. Use wherever a chalkboard finish is desired.

## General Description

Studio Finishes® Chalkboard paint (K307) is acrylic-based and turns virtually any interior surface into a chalkboard.

## Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F).

## Product Information

|  |  |  |  |   |
|--|--|--|--|---|
| <b>Colours — Standard:</b><br>Black  |  | <b>Technical Data</b> ▽  |  | <b>Black</b>                                    |
|  |  | Vehicle Type   |  | 100% Acrylic                                    |
|  |  | Pigment Type   |  | Carbon Black                                    |
|  |  | Volume Solids  |  | 40%   |
| <b>— Tint Bases:</b><br>None   |  | Coverage per 946 ml at<br>Recommended Film Thickness   |  | 9.27-10.4 sq. metres<br>(100-110 sq. ft.).      |
|  |  | Recommended Film Thickness   |  | — Wet 3.5 mils<br>— Dry 1.7 mils                |
| <b>— Special Colours:</b><br>None  |  | Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.                |  |   |
| <b>Certification</b><br><br>VOC compliant in all regulated areas.<br><br>Very low in VOC's   |  | <div>Qualifies for<br/><b>LEED®</b><br/><b>Credit</b><br/>(INTERIOR NON-FLAT)</div>  |  |   |
| <b>Customer Service Information Centre:</b><br>1-800-361-5898, <a href="mailto:info@benjaminmoore.ca">info@benjaminmoore.ca</a> , <a href="http://www.benjaminmoore.ca">www.benjaminmoore.ca</a> |  | Dry Time @ 25 °C (77 °F) @ 50% RH  |  | — To Touch 2 Hours<br>— To Recoat 4 Hours       |
|  |  | Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times. <b>ALLOW TO CURE 3 DAYS BEFORE USING AS A CHALKBOARD.</b> |  |   |
|  |  | Dries By   |  | Evaporation, Coalescence                        |
|  |  | Viscosity  |  | 95 ± 2 KU                                       |
|  |  | Flash Point  |  | None  |
|  |  | Gloss / Sheen  |  | Eggshell  |
|  |  | Surface Temperature at Application   |  | — Min. 10 °C (50 °F)<br>— Max. 32.2 °C (90 °F)  |
|  |  | Thin With  |  | Clean Water                                     |
|  |  | Clean Up Thinner   |  | Clean Water                                     |
|  |  | Weight Per 3.79 L  |  | 4.8 kg (10.4 lbs)                               |
|  |  | Storage Temperature  |  | — Min. 4.4 °C (40 °F)<br>— Max. 32.2 °C (90 °F) |
|  |  | <b>Volatile Organic Compounds (VOC)</b><br><br>20 g/L  |  |   |



## Customer Service Information Centre:

1-800-361-5898, [info@benjaminmoore.ca](mailto:info@benjaminmoore.ca), [www.benjaminmoore.ca](http://www.benjaminmoore.ca)

◇ Reported values are for Black. Contact Benjamin Moore for values of other bases or colours.

## **Surface Preparation**

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture\\_e.html](http://www.hc-sc.gc.ca/iyh-vsv/prod/paint-peinture_e.html).

## **Primer/Finish Systems**

Use the appropriate Fresh Start® primer if a primer is required. Follow label directions. For best results when significant colour change is desired, tint the primer to the approximate base colour. For previously painted surfaces in good condition, apply one or two coats of this product. Otherwise, before and after filling in nail holes, cracks and other surface imperfections, spot prime with this product. When dry, apply one or two finish coats of Studio Finishes® Chalkboard paint (K307).

## **Application**

Stir thoroughly. Apply one or two coats. For best results, use a Benjamin Moore® custom-blended nylon/polyester brush, Benjamin Moore® roller, or a similar product. This product can also be sprayed. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 10 °C (50 °F).

## **Thinning/Cleanup**

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or provincial environmental agency on disposal options.

## **Environmental, Health & Safety Information**

**Use only in a well ventilated area.** Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Material Safety Data Sheet for  
additional health and safety information.**