

Material Safety Data Sheet

Revision Date: 07-Jun-2011 Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name SUPER SPEC HP FAST DRY EPOXY FLOOR SEALER / FINISH

Product Code P4100

Product Class WATERBORNE EPOXY

Color Clear

Manufacturer Emergency Telephone Number(s)

Benjamin Moore & Co. CHEMTREC: 800-424-9300
101 Paragon Drive

Montvale, NJ 07645 Phone: 201-573-9600 www.benjaminmoore.com

2. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Components

Chemical Name	CAS-No	Weight % (max)	
Polyamide		20	
Propylene glycol monomethyl ether	107-98-2	5	

3. HAZARDS IDENTIFICATION

Emergency Overview

WARNING

Severe eye irritation. Irritating to skin. Irritating to respiratory system. Vapors may be irritating to eyes, nose, throat, and lungs. May cause sensitization by skin contact.

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, a small amount of clean sand may be added. Stir often during application.

Appearance liquid Odor ammonia-like

Potential Health Effects

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Effects

P4100 - SUPER SPEC HP FAST DRY EPOXY FLOOR SEALER / FINISH

Eyes Severe eye irritation. Risk of serious damage to eyes.

Skin Moderate skin irritation. May cause skin sensitization. Repeated or prolonged skin

contact may cause allergic reactions with susceptible persons.

Inhalation Inhalation of high vapor / aerosol concentrations may cause irritation of respiratory

system.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic Effects Avoid repeated exposure. Repeated contact may cause allergic reactions in very

susceptible persons. Prolonged exposure may cause chronic effects.

Revision Date: 07-Jun-2011

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Asthma and other respiratory disorders. Skin allergies. Skin disorders.

HMIS Health: 2 Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special"

handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has choosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact

lenses and continue flushing for at least 15 minutes. Keep eye wide open while

rinsing. Call a physician immediately.

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes. If symptoms persist, call a physician.

Inhalation Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial

respiration. Call a physician immediately.

Ingestion Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting

without medical advice. Never give anything by mouth to an unconscious person.

Consult a physician.

Notes To Physician Treat symptomatically.

Protection Of First-Aiders Use personal protective equipment.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective Equipment And Precautions For Firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 07-Jun-2011

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or extreme

heat.

Sensitivity To Mechanical Impact No

Sensitivity To Static Discharge No

Flash Point Data

Flash Point (°F)

Flash Point (°C)

Flash Point Method

Not applicable

Not applicable

Flammability Limits In Air

Lower Explosion LimitNot applicableUpper Explosion LimitNot applicable

NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsUse personal protective equipment. Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Environmental Precautions Prevent further leakage or spillage if safe to do so.

Methods For Clean-Up

Soak up with inert absorbent material. Sweep up and shovel into suitable containers

for disposal.

Other Information None known

7. HANDLING AND STORAGE

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or Handling

sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Revision Date: 07-Jun-2011

Storage Keep container tightly closed. Keep out of the reach of children.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

Hazardous Components

Chemical Name	ACGIH	OSHA	
Polyamide	N/E	N/E	
Propylene glycol monomethyl ether	100 ppm - TWA 150 ppm - STEL	N/E	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

OSHA - Occupational Safety & Health Administration Exposure Limits

N/E - Not Established

Ensure adequate ventilation, especially in confined areas. **Engineering Measures**

Personal Protective Equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting

safety goggles.

Skin Protection

Long sleeved clothing. Protective gloves. **Respiratory Protection**

In case of insufficient ventilation wear suitable respiratory equipment.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing

before re-use. Wash thoroughly after handling. When using, do not eat, drink or

smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid Odor ammonia-like Density (lbs/gal) 8.4 - 8.5**Specific Gravity** 0.95 - 1.05Not available pН Not available **Evaporation Rate Vapor Pressure** Not available **Vapor Density** Not available Wt. % Solids 10 - 20 Vol. % Solids 10 - 20 Wt. % Volatiles 80 - 90 Vol. % Volatiles 80 - 90 **VOC Regulatory Limit (g/L)** < 250

Revision Date: 07-Jun-2011

	9. PHYSICAL AND CHEMICAL PROPERTIES
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing Point (°F)	32
Freezing Point (°C)	0
Flash Point (°F)	Not applicable
Flash Point (°C)	Not applicable
Flash Point Method	Not applicable
Upper Explosion Limit	Not applicable
Lower Explosion Limit	Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions. Hazardous polymerisation

does not occur.

Conditions To Avoid Prevent from freezing

Incompatible Materials mineral acids, bases, oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating

gases and vapors.

Possibility Of Hazardous Reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product

No information available

Component

Polyamide

Sensitization: May cause sensitization by skin contact

Propylene glycol monomethyl ether

LD50 Oral: 6,600 mg/kg (Rat)

LD50 Dermal: 13,000 mg/kg (Rabbit) LC50 Inhalation (Vapor): 10,000 ppm (Rat)

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Revision Date: 07-Jun-2011

Ecotoxicity Effects

Product

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Component

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

United States TSCA

Canada DSL

Yes - All components are listed or exempt. Yes - All components are listed or exempt.

15. REGULATORY INFORMATION

Revision Date: 07-Jun-2011

Federal Regulations

SARA 311/312 hazardous categorization

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

This product may contain trace amounts of (other) SARA reportable chemicals. Contact the preparer for further information.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

This product may contain trace amounts of (other) HAPs chemicals. Contact the preparer for further information.

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Louisiana	Rhode Island
Propylene glycol monomethyl	X	Х	Х		X
ether					

Legend

X - Listed

16. OTHER INFORMATION

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

P4100 - SUPER SPEC HP FAST DRY EPOXY FLOOR SEALER / FINISH

Revision Date: 07-Jun-2011

Prepared By Product Stewardship Department

Benjamin Moore & Co.

360 Route 206 - P.O. Box 4000

Flanders, NJ 07836

866-690-1961

Revision Date: 07-Jun-2011 **Revision Summary** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of MSDS